



# XY-218HS

XY Series

## DUAL 18-INCH HORN-LOADED SUBWOOFER

The new horn-loaded XY-218HS is designed to deliver ultra-low frequencies at the high sound pressure level (SPL) needed for large venues and outdoor events.

## KEY FEATURES

- Dual 18-inch LF drivers with 4-inch voice coils
- Fully horn-loaded
- Fast attacking bass response (32 Hz to 150 Hz)
- Premium multi-laminate birch plywood enclosure
- Stackable design with recessed stacking slots
- Front and side handles
- Optional castors
- Perfect complement to the XY-122 and XY-152 two-way speakers
- Available in black or white

## APPLICATION

Large nightclubs / Outdoor events

## SPECIFICATIONS

|                           |   |
|---------------------------|---|
| Enclosure type            | Dual driver, horn-loaded subwoofer  |
| Frequency response        | 32 Hz to 150 Hz   |
| Sensitivity (1 W/1 m)     | 107.5 dB (half space)   |
| Nominal Impedance         | 4 Ω   |
| Power Handling            | 1400 W RMS, 2800 W Program  |
| Maximum SPL               | 139 dB cont., 145 dB peak (half space)  |
| Driver Configuration      | 2 × 18 inch/4" voice coil LF cone drivers   |
| Connectors                | 2 × Neutrik SpeakON™ NL4  |
| Dimensions (W × H × D)    | 1308 mm × 558 mm × 890 mm (51.2 × 21.7 × 35 inch)   |
| Weight                    | 134 kg (296 lbs)  |
| Rigging and Hardware      | 12 × flush handles (4 left/4 right/2 top/2 bottom), 10 × rubber feet (6 bottom and 4 left) and 6 × mating recesses (top), 16 × M8 holes with pre-inserted bolts for 4 × castors on rear |
| Grille                    | Hex punched steel   |
| Enclosure                 | 18 mm (0.7 inch) birch plywood  |
| Finish                    | Impact-resistant, Black semi-matt textured  |
| Suggested Power Amplifier | Recommended:K10DSP<br>Minimum:K6DSP   |